



F&F Filipowski sp.k., ul. Konstantynowska 79/81, 95-200 Pabianice, tel.: +48 (42) 214 90 37, e-mail: biuro@fif.com.pl, www.fif.com.pl



CP-721-FPV

Programmable voltage relay

Index: CP-721-FPV



5 902431 675077 >

TECHNICAL DATA

Depth	65 mm
Height	90 mm
Width	35 mm
Rated switch current	8 A
Number of contacts as change-over contact	2
Number of contacts as normally open contact	0
Number of contacts as normally closed contact	0
Max. permitted off-delay time	10 s
Min. adjustable off-delay time	2 s
Max. permitted delay-on energization time	1 s
Min. adjustable delay-on energization time	0.1 s
With detachable clamps	No
External power supply required	No
Response value voltage	150-260 V
Single-phase under voltage possible	Yes
Three-phase under voltage possible	No

Single-phase overvoltage possible	Yes
Three-phase overvoltage possible	No
Single-phase hysteresis possible	Yes
Three-phase hysteresis possible	No
Contains function DC-under voltage	No
Contains function DC overvoltage	No
Contains function DC-voltage hysteresis	No
Type of electric connection	Screw connection
Voltage type (supply voltage)	AC
Type of voltage measuring range	AC
Voltage type (operating voltage)	AC

Manual

CE Declaration