

COMMERCIAL BATTERY

E-MATE 112R-257R

High Voltage 112.5 ~ 257.2 kWh

UN38.3



Features



Scalable Capacity Up
to 257 kWh



Zero-Maintenance
Air Cooling



Industrial-Grade
Mechanical Design



High-Safety
LFP Cell System



Intelligent
Monitoring & O&M



Rapid Plug-and-Play
Deployment



Scenarios



Industrial Parks



Commercial Parks



Livestock Farms



Farms



Manufacturing Bases

DATASHEET

Model	E-MATE-112R E-MATE-192R	E-MATE-128R E-MATE-208R	E-MATE-144R E-MATE-225R	E-MATE-160R E-MATE-241R	E-MATE-176R E-MATE-257R
Performance					
Cell technology	LFP (LiFePO ₄)				
Battery module	16.0768 kWh, 51.2 V, 115 kg (253.53 lb)				
Number of modules	7	8	9	10	11
	12	13	14	15	16
Battery usable energy [1]	112.5376 kWh	128.6144 kWh	144.6912 kWh	160.768 kWh	176.8448 kWh
	192.9216 kWh	208.9984 kWh	225.0752 kWh	241.152 kWh	257.2288 kWh
System nominal voltage	358.4 V	409.6 V	460.8 V	512 V	563.2V
	614.4 V	665.6 V	716.8 V	768 V	819.2 V
System operating voltage	313.6 ~ 403.2 V	358.4 ~ 460.8 V	403.2 ~ 518.4 V	448 ~ 576 V	492.8 ~ 633.6 V
	537.6 ~ 691.2 V	582.4 ~ 748.8 V	627.2 ~ 806.4 V	672 ~ 864 V	716.8 ~ 921.6 V
System Max. charge and discharge current	157 A				
Recommended Depth of Discharge	90%				
Communication					
Display	LCD Display (battery operating status, SOC, alerts, etc.)				
Communication	CAN / RS485 / Bluetooth / Wi-Fi				
General Specification					
Dimension (W × D × H)	1052 × 802 × 1776 mm				1573 × 802 × 1502 mm
	1573 × 802 × 1502 mm	1573 × 802 × 1776 mm			
	41.42 × 31.57 × 69.92 inch				61.93 × 31.57 × 59.13 inch
	61.93 × 31.57 × 59.13 inch	61.93 × 31.57 × 69.92 inch			
Weight	1020 kg (2248.71 lb)	1140 kg (2513.27 lb)	1260 kg (2777.82 lb)	1380 kg (3042.38 lb)	1520 kg (3351.02 lb)
	1640 kg (3615.58 lb)	1760 kg (3880.13 lb)	1880 kg (4144.69 lb)	2000 kg (4409.24 lb)	2120 kg (4673.79 lb)
Installation	Floor stand				
Operating temperature [2]	Charge: 0°C ~ 55°C (32°F ~ 131°F) Discharge:-20°C ~ 55°C (-4°F ~ 131°F)				
Environmental humidity	≤ 95%RH (No condensation)				
Ingress protection rating	IP20				
Warranty period [3]	5 years / 10 years (Optional)				
Scalability	Max. 16 modules per stack, 9 stacks in parallel				
Cooling method	Natural cooling				
Application	ON Grid / ON Grid + Backup / OFF grid				
Compatible inverters	Refer to compatible Hybrid Inverter list				
Cycle life	8000 cycles (25±2°C, 0.5P / 0.5P, 70% SOH)				
Battery Cabinet — Hybrid Inverter Cable Specs	1/0 AWG (Copper Core Power Cable)				
Standard Compliance					
Compliance	UN38.3 / IEC62619 / 63056 / 60730 / IEC61000-6-2 / IEC62477-1				
Ordering and Delivery Parts					
	E-MATE-16-QC				
Battery Control Unit	E-MATE-BCU-M-112-QC	E-MATE-BCU-M-128-QC	E-MATE-BCU-M-144-QC	E-MATE-BCU-M-160-QC	E-MATE-BCU-M-176-QC
	E-MATE-BCU-M-192-QC	E-MATE-BCU-M-208-QC	E-MATE-BCU-M-225-QC	E-MATE-BCU-M-241-QC	E-MATE-BCU-M-257-QC
Battery Rack	E-MATE-R12	E-MATE-R12	E-MATE-R12	E-MATE-R12	E-MATE-R15
	E-MATE-R15	E-MATE-R18	E-MATE-R18	E-MATE-R18	E-MATE-R18

[1] Test conditions: 100% depth of discharge (DOD), 0.5C rate charge & discharge at 25°C.

[2] Charge / discharge derating occurs when the temperature is below 0°C or above 45°C.

[3] Please refer to the Warranty Letter for applicable conditions.