



Hyper-ion Pro

Heterojunction Hyper-ion Series Bifacial Module

RSM132-8-720-740BHDG

Hyper-link Interconnection

Patented Technology

720-740 Wp

Power Output Range

23.8%

Higher Efficiency

0~+3%

Positive Power Tolerance



The module picture is for reference only



No B-O caused LID



Ultra-high bifacial factor



Ultra-high power generation, ultra-low carbon emission



Most stable power temperature coefficient



Lead technology of metallization process



Excellent anti-LID & anti-PID performance




* As there are different certification requirements in different markets, please contact your local Risen Energy sales representative for the specific certificates applicable to the products in the region in which the products are to be used.

LINEAR PERFORMANCE WARRANTY


15 years product warranty / 30 years linear power warranty

0.3% Annual Degradation over 30 years




*Please check the valid version of Limited Product Warranty which is officially released by Risen Energy Co., Ltd

Unit: 100




RSM132-8-730BHDG

I-V characteristics at different irradiations



I-V characteristics at different temperatures

(AM1.5, 1000W/m²)

Model Type	RSM132-8-720-740BHDG				
Rated Power in Watts-Pmax(Wp)	720	725	730	735	740
Open Circuit Voltage-Voc(V)	50.18	50.26	50.33	50.40	50.47
Short Circuit Current-Isc(A)	18.19	18.29	18.38	18.47	18.56
Maximum Power Voltage-Vmpp(V)	42.08	42.14	42.20	42.26	42.32
Maximum Power Current-Impp(A)	17.13	17.23	17.32	17.41	17.50
Module Efficiency (%) ★	23.2	23.3	23.5	23.7	23.8

Bifacial factor: $90 \pm 5(\%)$ ★ Module Efficiency (%): Rounding to the nearest number

Total Equivalent power -Pmax (Wp)	792	798	803	809	814
Open Circuit Voltage-Voc(V)	50.18	50.26	50.33	50.40	50.47
Short Circuit Current-Isc(A)	20.01	20.12	20.22	20.32	20.42
Maximum Power Voltage-Vmpp(V)	42.08	42.14	42.20	42.26	42.32
Maximum Power Current-Imp(A)	18.84	18.95	19.05	19.15	19.25

ELECTRICAL DATA (NMOT)

Model Type	RSM132-8-720-740BHDG				
Maximum Power-Pmax (Wp)	550.0	554.0	557.7	561.3	565.0
Open Circuit Voltage-Voc (V)	47.02	47.09	47.16	47.22	47.29
Short Circuit Current-Isc (A)	14.92	15.00	15.07	15.15	15.22
Maximum Power Voltage-Vmpp (V)	39.34	39.40	39.46	39.51	39.57
Maximum Power Current-Imp (A)	13.98	14.06	14.13	14.21	14.28

MECHANICAL DATA

Solar cells	<i>n</i> -type HJT
Cell configuration	132 cells (6×11+6×11)
Module dimensions	2384×1303×33mm (93.86×51.30×1.30 in)
Weight	37.5kg (82.67 lb)
Superstrate	2.0mm(0.08in), High Transmission, AR Coated Heat Strengthened Glass
Substrate	2.0mm(0.08in), Heat Strengthened Glass
Frame	Anodized Aluminium Alloy, Silver Color
J-Box	Potted, IP68, 1500VDC, 3 Schottky bypass diodes
Cables	4.0mm ² , 350mm(13.78 in)(+), 230mm(9.06 in)(-), connector Included, or customized length
Connector	PV-SY02/Others
Maximum mechanical test load	5400 Pa (front) / 2400 Pa (back), under certain installation method

TEMPERATURE & MAXIMUM RATINGS

Nominal Module Operating Temperature (NMOT)	43°C ± 2°C
Temperature Coefficient of Voc	-0.22%/°C
Temperature Coefficient of Isc	0.047%/°C
Temperature Coefficient of Pmax	-0.24%/°C
Operational Temperature	-40°C ~ +85°C
Maximum System Voltage	1500VDC
Max Series Fuse Rating	35A
Limiting Reverse Current	35A

PACKAGING CONFIGURATION

	40ft(HQ)
Number of modules per container	594
Number of modules per pallet	33
Number of pallets per container	18
Packaging box dimensions (LxWxH) in mm	1320 × 1125 × 2520
Box gross weight[kg]	1289



Website: www.risen.com

THE POWER OF RISING VALUE

No special undertaking or warranty for the suitability of special purpose or being installed in extraordinary surroundings is granted unless as otherwise specifically committed by manufacturer in contract document.

Version: REM132-BHDG-0BB-EN-H1-2-2025-Pro