



Q-SUN solar

Qrystal **N8**

Mono-Crystalline 460~480W

0~+5W POWER TOLERANCE

- High efficiency N - type double glass solar module
- Stronger properties, PID resistance, reduced hot spot loss
- Higher module power, lower BOS costs
- Harsh environmental adaptation
- Bifacial module, more power generation

15 years material warranty



30 years power linear warranty



120

HALF-CUT
CELLS

182
x183.75
mm

RECTANGULAR
CELLS

**A sound quality management
system and product certification**

IEC61215(2016), IEC61730(2016)

ISO9001:2015: Quality management system

ISO14001:2015: Environmental management system

ISO45001:2018: Occupational health and safety management system




22.2%
MAXIMUM CONVERSION

0~+5W
POWER TOLERANCE

0.4%
0.4% PER YEAR OVER 30 YEARS

Half-Cut Module
LOWER TEMPERATURE COEFFICIENT

Mechanical Diagrams



Length: ±2mm Width: ±2mm Thickness: ±1mm Hole pitch: ±2mm

Packing Standard

Container capacity(40HQ)

Pallet size (mm) : 36pcs/pallet, 24pallets/ctns, 864pcs/ctn

Electrical Parameters At BNPI

Maximum Power (Pmax)	507	513	518	524	529
Open Circuit Voltage (Voc)	42.43	42.71	43.00	43.27	43.54
Short Circuit Current (Isc135)	15.13	15.19	15.26	15.32	15.38
Maximum Power Voltage (Vmp)	35.38	35.63	35.88	36.12	36.36
Maximum Power Current (Imp)	14.33	14.39	14.44	14.50	14.55
Short Circuit Current (Isc300)	16.85	16.92	16.99	17.06	17.13

Electrical Parameters

Module Type	QN-460HT-05		QN-465HT-05		QN-470HT-05		QN-475HT-05		QN-480HT-05	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax)	460	348	465	352	470	355	475	359	480	363
Open Circuit Voltage (Voc)	42.43	40.31	42.71	40.57	43.00	40.85	43.27	41.11	43.54	41.36
Short Circuit Current (Isc)	13.72	10.98	13.78	11.02	13.84	11.07	13.90	11.12	13.95	11.16
Maximum Power Voltage (Vmp)	35.38	33.43	35.63	33.67	35.88	33.91	36.12	34.13	36.36	34.36
Maximum Power Current (Imp)	13.00	10.40	13.05	10.44	13.10	10.48	13.15	10.52	13.20	10.56
Module Efficiency -ηm (%)	21.3		21.5		21.7		22.0		22.2	


Load Capacity

Max Load Front	5400Pa
Max Load Back	2400Pa
Through Hail Testing	25mm Diameter, Impact Speed 23m/s

Temperature Coefficient (STC Test)


Temperature Coefficient of Isc	+0.04%/°C
Temperature Coefficient of Voc	-0.25%/°C
Temperature Coefficient of Pmax	-0.30%/°C

Curve Figure



Specification

Cell Type	Mono Crystalline
No. of Cells	120 [2x(6x10)] pcs
Dimension	1909×1134×30 mm
Weight	26.5kg
Front Glass	2.0mm
Back Glass	2.0mm
Junction Box	IP68
Cable Length	300mm,1200mm(can be customized)



Operation Parameters

Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500VDC (IEC)
Maximum Series Fuse Rating	25A
Power Tolerance	0~+5W
Nominal Operating Cell Temperature (NOCT)	42±2°C
Safety Class	Class II
Fire Safety Class According	Class C

STC : Irradiance:1000W/m² | Battery temperature: 25°C | Atmospheric=1.5

NOCT : Irradiance:800W/m² | Ambient temperature: 20°C | Atmospheric=1.5 | Wind speed 1m/s

BNPI : Rear Irradiance 135W/m² | Bifaciality coefficient 80%±5%

D5 Greenland Window Building
Nonghua Road
Yuhuatai District, Nanjing, China
www.q-sunsolar.com



All data contained in this specification is subject to change without prior notice, and the final interpretation rights belong to Q-SUNSOLAR (20240423V2)