

BluePulse Series NEW

KAC(80~125)DP2-BC220DE2A / BC240DE2A / BC260DE2A

Versatile Application

- ▶ Ideal for factories, hotels, and farms with DC / AC-coupled solar-storage
- ▶ No external switching device is required, on/off-grid switching time about 10ms, support direct output backup load

Safe & Reliable

- ▶ 314ah large capacity cell, higher energy density
- ▶ Carbon monoxide detection, Sound and light alarm, Exhaust fan, Explosion vent window, Inlet valve, Fire water injection port

Smart Energy

- ▶ Supports self-consumption, peak shifting, time-of-use, and battery backup
- ▶ Integrated self-developed BMS / EMS for flexibility

High Performance

- ▶ Small size, small footprint
- ▶ Long-lasting battery cycle life

Easy Operation

- ▶ Compact design saves space
- ▶ Cloud control with 24 / 7 monitoring



Technical Parameters	BC220DE2A		BC240DE2A		BC260DE2A	
Battery Type	LiFe (LiFePO4)					
Battery Module Capacity	20.09 kWh					
Number of Modules	11		12		13	
Total Battery Capacity	221.05 kWh		241.15 kWh		261.24 kWh	
Nominal Voltage	704 V		768 V		832 V	
Operating Voltage Range	627 ~ 792 V		684 ~ 864 V		741 ~ 936 V	
Charge / Discharge Rate	0.5 C					
Standard Charging / Discharging Current	157 A / 157 A					
DoD	90%					
Product Specifications	KAC80DP2	KAC100DP2		KAC110DP2	KAC125DP2	
Max. Battery Charge / Discharge Power	88 kW	110 kW		110 kW	125 kW	
General Parameters						
Dimensions (W x H x D)	1324 x 1440 x 2415 mm					
Weight	< 2.39 T		< 2.53 T		< 2.66 T	
Installation Site	Outdoor					
IP Protection	IP54					
Anti Corrosion Level	C4					
Operation Humidity	0 ~ 95% (No Condensing)					
Operation Temperature	-30°C ~ +50°C					
Max. Operation Altitude	≤ 3000 (> 2000m Derating)					
Communication Port	Ethernet; CAN					
Communication Protocol	CAN; TCP					
Cooling Method	Intelligent Air Cooling					
Warranty	5 Year Product Waaarranty; 10 Year Performance Warranty					
Certificates	UL 9540A; UN38.3; MSDS; IEC 62040; IEC 62477; IEC 62619; IEC 63056; IEC 61000-6-2/4					

Hybrid Inverter Parameters

Product Specifications	KAC80DP2		KAC100DP2	KAC110DP2	KAC125DP2
PV Side					
MPPT Voltage Range	250 ~ 950 V (Max. 1000 V)				
MPPT Rated Voltage	720 V				
MPPT Rated Voltage (Full Load)	450 ~ 800 V	550 ~ 800 V	600 ~ 800 V	700 ~ 800 V	
Max. PV Power	160 kWp	200 kWp	220 kWp	250 kWp	
Number of MPPT / Strings per MPPT	8 / 2				
Max. Current per MPPT	45 A				
Battery Side					
Battery Voltage Range	200 ~ 950 V				
Battery Rated Voltage Range	250 ~ 800 V				
Max. DC Current	160 A (80 A x 2)				
Max. DC Power	88 kW	110 kW	110 kW	125 kW	
Number of DC Inputs	2				
AC Side (On Grid)					
Nominal AC Output Power	80 kW	100 kW	110 kW	125 kW	
Max. AC Output Power	88 kVA	110 kVA	121 kVA	125 kVA	
Rated AC Output Current	116 A	144 A	159 A	181 A	
Max.AC Input Current	227 A	227 A	227 A	227 A	
AC Rated Voltage / Voltage Range	230 / 400 Vac; 220 / 380 Vac; 3L+PE+N; -15% ~ +10%				
Nominal Grid Frequency / Frequency Range	50 Hz / 60 Hz (±5 Hz)				
THDi	< 3% (100% Load)				
Adjustable PF Range	0.8 inductive(under-excited) to 0.8 capacitive(over-excited)				
Backup Output					
Nominal AC Voltage	230 / 400 V; 220 / 380 Vac; 3L+PE+N				
THDv	< 3% (Rated Power)				
Nominal Grid Frequency / Frequency Range	50 Hz / 60 Hz				
Nominal AC Output Power	80 kW	100 kW	110 kW	125 kW	
Max. AC Output Power (Single-phase)	50 kW				
Max. Output Current	227 A				
Genset Input					
Max. Input Current	227 A				
Efficiency					
Max. Efficiency	98%				
Protection					
Reverse DC Connection Protection	Yes				
Anti-Islanding Protection	Yes				
Over-Temperature Protection	Yes				
Grid Monitoring / Earthing Fault Detection	Yes				
Insulation Monitoring	Yes				
DC / AC Surge Protection	DC Type II; AC Type II				
AFCI	Optional				
General Parameters					
Dimensions (W x H x D)	1120 x 760 x 365 mm				
Weight	135 kg				
Topology	Transformerless				
IP Protection	IP65				
Operation Temperature Range	-25 ~ 60°C (> 45°C Derating)				
Operation Humidity Range	0 ~ 100% (No Condensing)				
Cooling Method	Intelligent Air Cooling				
Max. Operation Altitude	4000 m (> 3000 m Derating)				
Communication Port	RS-485 / CAN				