

GUANGDONG CABLE FACTORY CO.,LTD


RM704, WANDA PLAZA, GUILAN ROAD, GUICHENG, FOSHAN, GUANGDONG, CHINA

CONTACT : TERIWONG Mobile: 0086-18038777098

TEL: +86 757 8631 5127 FAX: +86 757 8640 0177

Email: vazpok@vazpocable.com Website: www.3acable.com

SPECIFICATION

Client's number/客户编号		Table no./表格编号	
Type/型号	H1Z2Z2-K		
Size/尺寸	1 X 6mm ²	Construction details	
Standard/标准	EN 50618:2014	Product picture	
Conductor / 导体			
Construction/结构(mm ²)	84/0.28		
Material/材料	Tinned copper	Crossing section	
O.D/外径(mm)	2.96	Cable printing:	
Insulation / 绝缘		Guangdong cable Co. Ltd, + AAA logo EN50618 H1Z2Z2-K	
Material/材料	XLPO	DC1.5KV 1*6mm ² + Metering	
Average thickness/平均厚度(mm)	0.75		
O.D/外径(mm)	4.43 ± 0.15		
Color/颜色	RED / Black	Package selection / 包装选择	
Jacket / 护套			
Material/材料	XLPO		
Average thickness/平均厚度(mm)	0.85	Film	
O.D/外径(mm)	6.40±0.2	Wooden drum	
Color/颜色	Red / Black	Wooden roller	
Electric Performance / 电气性能		Film + pallet	
Rated voltage/额定电压	DC 1500V	Wooden drum + pallet	
Range of temperature 温度范围(°C)	-40~125	Wooden roller + pallet	
Dielectric strength/耐压强度	AC-6.5KV/1min	VERSION APPROVED DATE	
Spark test/火花测试	AC-10KV/In the air		
Resistance/电阻	3.39ΩKm		
UV resistance/抗紫外线	720h		
Live time	25 Years		
Mark / 标签			
Shipping mark	Client's provided		
Shipping data / 出口信息			
Weight(kg/km)	83		
500METERS CBM(m ³)	40X40x20cm		
HS Code	8544609090		
APPROVED	CHECKED		